



**Technical Data Sheet For  
Gush Cair Fresh Interior Paint**

Established: 08 May 2019  
Updated: 5 Nov 2019

**PRODUCT DESCRIPTION :**

Gush cair fresh interior paint is a premium acrylic emulsion with smooth highly decorative and attractive rich matte finish. It helps purify that air for healthier living conditions. Apart from that, the paint has zero formaldehyde and nearly zero VOC content unlike traditional paints. gush cair fresh interior paint is a new generation odourless paint that purifies the indoor air pollutants and it has anti-mold & bacterial properties.

**PRODUCT TYPE:**

Water-based Interior Emulsion paint

**COLOR:**

As per gush color card

**FINISH:**

Matt

**DESIGN USE:**

1. Ideally suited for internal new & repainting masonry surfaces, such as cement, plastered walls and fiber boards.
2. Can also be used on areas like void decks and common corridor.
3. It is also suitable on other properly primed surfaces.

**PRODUCT FEATURES:**

- ✓ Extremely low VOC (<2 g/L)
- ✓ Odourless
- ✓ Purifies Air
- ✓ Anti - Bacterial
- ✓ Anti - Molding
- ✓ Quick Drying
- ✓ Easy Application

**APPLICATION DETAILS:**

**METHOD:** Roller, brush and paint sprayer

**THEORETICAL COVERAGE:** 10 – 12 m<sup>2</sup> / litre (30 microns DFT)

**DILUTION:** Not more than 10% dilution with water.

**SURFACE PREPARATION:** Ensure surface is clean, dry and stable using the following suggested surface treatments:

**Moisture:** There must not be any water residue on the surface of the substrate. Moisture must be <5% (moisture content meter) before application.

**Unstable matter:** Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable.

**Contaminants:** Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry.

**Fungus and Algae:** Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours.

**Hairline cracks:** Fill cracks with suitable exterior grade water- resistant putty or filler.

**DRYING TIME:**

Touch Dry - 30 minutes at 25 °C

**OVER-COATING TIME:**

Minimum over-coating interval: 2 hours at 25 °C

**CLEANING SOLVENT:**

Clean water

**SOLID CONTENT:**

52 ± 2% by weight (based on white)

**SPECIFIC GRAVITY:**

1.42 ± 2% by kg/litre (based on white)

**PACKAGING:**

5 Litres

20 Litres

**PRECAUTION-READ PRECAUTION INSTRUCTION BEFORE USE:**

1. Use appropriate personal protective equipment before application.
2. Avoid direct contact with sensitive skin.
3. Ensure good ventilation during application and drying of paint.
4. Keep out of reach of children.
5. Do not store near food or other articles intended for consumption by humans or animals.
6. Keep containers tightly closed at all times.
7. Do not allow product to enter drains and watercourses.
8. Do not reuse the container.

**DECLARATION:**

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

**Enquiries / Contact Details :**

2 Gambas Cres, #01-35 Nordcom II, Singapore 757044

HQ Office: 6692 9000 (Main Line)

Email: [hello@gowithgush.com](mailto:hello@gowithgush.com)

**[www.gowithgush.com](http://www.gowithgush.com)**